

FEATURES

- 30 Year Warranty
- Crawl Space Encapsulation® Approved
- Made from 100% Virgin Polyethylene
- 1000 Denier Polyester Cord Reinforced
- Made in America
- Anti-Microbial and Anti-Fungal Additive
- Lab Tested for VOC's, Odors and Off-Gassing
- Bright White Facing and Tan Backing



SPECIFICATIONS

PROPERTIES	AVERAGE VALUES
THICKNESS AT PLASTIC	Nominal 11 mil (0.28 mm) + 10%
THICKNESS AT STRING	Nominal 15 mil (0.38 mm) + 10%
WEIGHT	60 lb/msf
CONSTRUCTION	Extrusion Laminated with Scrim Reinforcement
**GRAB TENSILE	100 dbf
**ELONGATION AT SCRIM BREAK	16%
*TRAPEZOID TEAR	59 lbf
***TONGUE TEAR	54 lbf
CBR PUNCTURE RESISTANCE	276 lbf
PERM RATING	0.022 perms/(ft ² ·hr·in·Hg)
MAXIMUM STATIC USE TEMPERATURE	180° F
MINIMUM STATIC USE TEMPERATURE	-70° F

AVAILABLE IN:

- 36" x 75' - 225 sqft (12MGL-36) ■ 44" x 75' - 275 sqft (12MGL-44)
- 6'9" x 100' - 675 sqft (12MGL-100) ■ 13'4" x 50' - 675 sqft (12MGL-50)
- 13'4" x 75' - 1000 sqft (12MGL-75)

VISIT GUARDIANLINER.COM FOR MORE



*Tests are an average of diagonal directions.

**Tests are an average of machine and transverse direction.

***Tests are an average of primary reinforcement directions.

Note: To the best of our knowledge, unless otherwise stated, these are typical property values and are intended as guides only, not as specification limits. Chemical resistance, odor transmission, longevity as well as other performance criteria is not implied or given and actual testing must be performed for applicability in specific application and/or conditions. GUARDIANLINER® MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage.

LIMITED LIFETIME WARRANTY

GuardianLiner® Warrants that their products will be free from material defects and workmanship, under normal proper use, storage and operating conditions for thirty years. For full warranty information visit CrawlSpaceEncapsulation.com